

## Classifications

**EN ISO 3581-A**

E 19 12 3 L R 3 2

**AWS A5.4 / SFA-5.4**

E316L-17

## Characteristics and typical fields of application

Rutile coated, core wire alloyed electrode of E 19 12 3 L R / E316L-17 type. Preferably used for 1.4404 and 1.4435 / 316L austenitic stainless steel grades suitable in all industries using similar or high carbon steels or ferritic 13Cr-steels. Designed for first class weld seams and easy handling on AC or DC. High current carrying capacity with minimum spatter formation. Self-releasing slag, smooth and clean weld profile. Good resistance to general and pitting corrosion. Max. service temperature 400°C.

## Base materials

1.4401 X5CrNiMo17-12-2, 1.4404 X2CrNiMo17-12-2, 1.4409 GX2CrNiMo19-11-2, 1.4429 X2CrNiMoN17-12-3,

1.4432 X2CrNiMo17-12-3, 1.4435 X2CrNiMo18-14-3, 1.4436 X3CrNiMo17-12-3, 1.4571 X6CrNiMoTi17-12-2,

1.4580 X6CrNiMoNb17-12-2, 1.4583 X10CrNiMoNb18-12

UNS S31600, S31603, S31635, S31640, S31653

AISI 316L, 316Ti, 316Cb

## Typical analysis

|       | C    | Si  | Mn  | Cr   | Ni   | Mo  |
|-------|------|-----|-----|------|------|-----|
| wt.-% | 0.03 | 0.8 | 0.8 | 18.8 | 11.5 | 2.7 |

## Mechanical properties of all-weld metal - typical values (min. values)

| Condition | Yield strength R <sub>p0.2</sub> | Tensile strength R <sub>m</sub> | Elongation A (L <sub>0</sub> =5d <sub>0</sub> ) | Impact energy ISO-V KV J |
|-----------|----------------------------------|---------------------------------|---|--------------------------|
|           | MPa                              | MPa                             | %   | 20°C                     |
| u         | 460 ( $\geq$ 320)                | 590 ( $\geq$ 510)               | 41 ( $\geq$ 25)                                 | -120°C                   |

u untreated, as-welded

## Operating data

| Polarity<br>Electrode identification   | DC+ / AC<br>FOX EAS 4 M-A 316L-17 E 19<br>12 3 L R | Dimension mm | Current A |
|--|--|--------------|-----------|
|  |  | 1.5 × 250    | 25 – 40   |
|  |  | 2.0 × 300    | 40 – 60   |
|  |  | 2.5 × 250    | 50 – 90   |
|  |  | 2.5 × 350    | 50 – 90   |
|  |  | 3.2 × 350    | 80 – 120  |
|  |  | 4.0 × 350    | 110 – 160 |
|  |  | 4.0 × 450    | 110 – 160 |
|  |  | 5.0 × 450    | 140 – 200 |

Suggested heat input is max. 2.0 kJ/mm and interpass temperature max. 150°C.

Redrying if necessary at 250 – 300°C for min. 2 h.

## Approvals

TÜV (00773), DB (30.014.14), ABS, DNV, LR, CWB, RINA, CE